



The Cyclonix range of subwoofers are designed for edge-of-yourseat bass performance in dedicated home cinema rooms.

Their shallow depth allows them to be placed inconspicuously against a side or back wall as supporting subwoofers to a Series MX system. They can also be used as the main subwoofers in a dedicated home cinema system - either behind an acoustically transparent screen or elsewhere in the room.

The Cyclonix 15 has taken its design cues from the subwoofer modules in the MX-20 system, foregoing the acoustic absorbent material on the front baffle and instead offering an optional black cloth grille.

The large 380mm bass driver features a 100mm edge-wound copper voice coil, dual spider assembly and vented magnet assembly. The front-firing vent and high-sensitivity driver are tuned to achieve maximum output, resulting in an incredibly efficient subwoofer for high drive level applications. Proprietary Krix rubber feet provide improved acoustic isolation on hard and soft floor surfaces.

A separate power amplifier is required for this subwoofer and can be connected to the LFE output of any AV processor or receiver.

For the ultimate cinema experience at home, play it through Krix.

FEATURES

- Supporting subwoofer for Series MX systems
- Can also be used as a primary subwoofer
- Shallow design allows for greater placement options





| | Cyclonix 15 |
|---------------------------|---|
| Frequency Range | 25 Hz - 200 Hz (in room response) |
| Amplifier Power | 200 – 1400* Watts RMS recommended amplifier power * The use of a power amplifier with high pass filter and soft limiter function is strongly recommended on this subwoofer |
| Recommended Processing | High Pass Filter: 25 Hz 24dB / Octave Butterworth |
| | Limiter: 1000W (8 Ohms) |
| Sensitivity | 96 dB SPL (2.83V / 1m) |
| Impedance | 8 Ohms |
| Inputs | High current spring terminals featuring a 5mm hole to accept up to 10AWG cable |
| Low Frequency Driver | Single 380mm (15") paper cone driver. 100mm (4") edge-wound copper voice coil, dual spider assembly and vented magnet assembly |
| Enclosure Type | Bass reflex, front vented |
| Dimensions | 1015mm high x 550mm wide x 270mm deep (290mm deep with optional grille) |
| Net Weight | 38 kg |

DETAILED DIMENSIONS



