

## NEUPHONIX MK2 **FLOORSTANDING**

A big sound for your biggest space, whether playing the latest blockbuster movie or an album to rock the room. The Neuphonix Mk2 can handle the power, cooly, calmly, without taking up too much space.

With a sculpted front baffle designed to improve clarity, the Neuphonix Mk2 is a 3-way design featuring four custom-designed 130mm bass drivers, each with oversized magnets.

An extensive crossover network - featuring only low tolerance, high grade components - beautifully matches the 130mm dedicated midrange and the high grade 26mm ring radiator tweeter, delivering an extended frequency response to 40kHz.

A scalloped grille subtly augments the acoustic benefits of the baffle and adds extra style to an already streamlined design. The rear of the cabinet features a brushed aluminium terminal plate and gold plated brass binding posts.

Complete the look with your choice of premium cabinet finishes. Elegance is in the details.

For the ultimate sound experience at home, play it through Krix.

## **FEATURES**

- Deep, effortless bass
- Power, impact and finesse
- Design details that deliver



	Neuphonix Mk2
Frequency Range	35Hz - 40kHz (in room response)
Power Handling	50 - 300 Watts RMS recommended amplifier power
Sensitivity	88dB (2.83V / 1m)
Impedance	Nominal 6 Ohms (minimum 4.9 Ohms)
Configuration	3-way
Low Frequency Drivers	4 x nominal 130mm (5") coated paper cones. 26mm (1") voice coil wound on high powered aluminium former provides enhanced linearity. Oversized magnet for low distortion
Mid Frequency Driver	1 x nominal 130mm (5") coated paper cone. 26mm (1") voice coil wound on high powered aluminum former, using copper shorting ring and oversized magnet for low distortion
High Frequency Driver	26mm (1") dual concentric diaphragm with wave-guide centre plug for controlled directivity. Non-reflective dual chambered magnet structure with copper shorting ring to lower distortion
Enclosure Type	Dual chambers - sealed midrange chamber with bass reflex main chamber. Rear vented with internal and external flaring
Input Terminals	Dual gold plated bi-wire binding posts (bi-wireable, bi- ampable)
Dimensions	1046mm high x 225mm wide x 405mm deep (including grille)
Weight	30kg each



## **COMPLEMENTARY CENTRE CHANNEL**

For the ultimate movie experience. Ensuring perfect timbral matching with the Neuphonix Mk2, the Epicentrix Mk2 centre channel speaker features identical, high grade components with vertical mid and high frequency driver alignment, ensuring a seamless soundtage of crystal clear dialogue and bone-crunching effects.

## **FINISHES**







Atlantic Jarrah



Blackwood



krix.com